

07-24-00

A

SENNIGER, POWERS, LEAVITT & ROEDEL
ATTORNEYS AT LAW

ONE METROPOLITAN SQUARE
16TH FLOOR
ST. LOUIS, MISSOURI 63102
314-231-5400

FACSIMILE 314-231-4542
<http://www.senniger.com>
PATENTS, TRADEMARKS, COPYRIGHTS
AND RELATED MATTERS

OF COUNSEL
IRVING POWERS
DONALD G. LEAVITT
RICHARD G. HEYWOOD
ROBERT J. LEWIS

STUART N. SENNIGER
(1921-1997)

July 21, 2000

UTILITY PATENT APPLICATION TRANSMITTAL
(new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket Number: TDCI 4335
First Named Inventor: William Stuchlik et al.
Express Mail Label Number: EL302953467US

TO: Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

APPLICATION ELEMENTS

1. ☐ Fee Transmittal Form
(original and duplicate)
2. ☒ Specification [Total Pages 35]
3. ☒ Drawings [Total Sheets 7]
4. Oath or Declaration [Total Pages 6]
 - a. ☐ Newly executed (original or copy)
☒ New (unexecuted)
 - b. ☐ Copy from a prior application
(for continuation/divisional with
Box 17 completed)
 - i. ☐ DELETION OF INVENTOR(s)
Signed statement attached
deleting inventor(s) named
in prior application.
5. ☐ Incorporation By Reference
(useable if Box 4b is marked)

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above
copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☒ Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ IDS with PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard
14. ☐ Small Entity Statement(s)
☐ Statement filed in prior application; status still
proper and desired
15. ☐ Certified Copy of Priority Document(s) if foreign
priority is claimed
16. ☐ Other: _____

**IF A CONTINUING APPLICATION, CHECK APPROPRIATE
BOXES AND SUPPLY THE REQUISITE INFORMATION**

17. ☐ Continuation ☐ Divisional ☒ Continuation-in-Part
of prior application No.: 09/177,311, filed October 22,
1998.
- ☐ Complete Application based on provisional Application
No. _____

CORRESPONDENCE ADDRESS

18. Correspondence Address: Customer Number 321
Attention: Frank R. Agovino

Respectfully submitted,

Frank R. Agovino

Frank R. Agovino, Reg. No. 27,416

FRACwa

BRUSH HEAD POSITIONING SYSTEM

Cross Reference to Related Application

The instant application is a continuation-in-part of U.S. Serial 09/177,311, filed October 22, 1998.

5 Background of the Invention

1. Field of the Invention.

The invention generally relates to an apparatus for treating a surface which apparatus is responsive to an operator to position a head assembly relative to the
10 surface. In particular, the invention relates to a brush head positioning system for a floor scrubber in which the brush head carries rotating brushes for cleaning the floor and the position of the brush head relative to the floor is controlled.

15 2. Background of the Invention.

When scrubbing floors, it is important to maintain a constant and continuous scrubbing action on the floor. Often times, the floor surface is uneven, requiring some means for adjusting the brush head to follow the contours of
20 the floor surface. The goal is to provide an even scrub across the entire floor. Also, brushes and pads can wear or the operator may want to change to a different type of brush or pad with different heights. In any of these conditions, the brush head must be properly positioned to compensate for
25 such variations.

In the past, several attempts have been made to provide a floor scrubbing system which accomplishes the above. For example, in some systems, an operator must manually reposition the brush head depending on the various varying
30 factors noted above. It is also known that the torque of drive motors for driving brushes or other floor maintenance tools may be controlled in order to provide some type of consistency in the application of force to the floor. However, such torque control systems tend to adjust the

torque based on the type of surface of the floor or based on the condition of the floor. As an example, when scrubbing concrete the surface texture can change dramatically with only slight variations in floor height. Such a system may
5 over torque the application of a brush to a smooth concrete floor and may under torque the application of a brush to a rough concrete floor. In addition, a floor which has a sticky coating on it may be under torqued whereas a floor with a shiny coating on it may be over torqued. Therefore,
10 monitoring torque or current drawn on brush motors for positioning the brush head is not necessarily an effective technique for accomplishing consistency in the application of force to the floor. This is because the torque or current draw is dramatically affected by variations in the
15 friction between the brushes and the floor. Since the coefficient of friction of the surface may change dramatically, this causes similarly dramatic changes in the current or torque, which changes may be unacceptable. Changes in surface texture may or may not demand a change in
20 torque or current in order to maintain a proper and consistent floor treatment.

Other systems have suggested a load cell to measure pressure. However, such systems are expensive and difficult to implement in a reliable, industrial grade apparatus.
25 Therefore, there is a need for a system which consistently positions the brush head relative to the floor surface so that the position is repeatable thereby permitting the repeatable and consistent cleaning of the floor surface. There is also a need for a system which is
30 responsive to variations in the contours of floors so that height adjustments between the brush assembly and the floor can be accomplished automatically to compensate for such differences in floor height. There is also a need for such a positioning system that accommodates different side
35 brushes and pads.

Summary of the Invention

It is an object of the invention to provide a floor cleaning system which employs a brush head for engaging the floor which brush head has a position which is controlled
5 relative to the position of the floor.

It is an object of the invention to provide a brush head cleaning system which repeatedly positions the brush head relative to the floor.

It is another object of this invention to provide a
10 brush head cleaning system which is rugged and low in manufacturing costs but provides efficient positioning of the brush head assembly relative to the floor.

It is another object of this invention to provide a brush head cleaning system which permits the brush head to
15 be positioned and which also permits the torque of the brush to be controlled after the brush head is positioned.

It is another object of this invention to provide a brush head cleaning system which permits the brush head to be positioned and which provides pressure control of the
20 brush after the brush head has been positioned.

In one form, the invention comprises an apparatus for use on a surface and responsive to an operator. A vehicle is adapted to ride on the surface. A head assembly is adapted to carry a device for engaging and treating the
25 surface. A connector assembly interconnects the head assembly and a support. An actuator on the vehicle raises and lowers the support relative to the surface. A sensor detects a distance between the support and the head assembly. A head position control, responsive to input from
30 the operator, indicates a desired position of the head assembly relative to the support. A driving circuit responsive to the head position control and responsive to the sensor energizes the actuator to raise and lower the support so that the distance between the support and the
35 head assembly as detected by the sensor corresponds to the desired position as indicated by the head position control

thereby controlling the relative engagement between the head assembly and the surface and thereby controlling the treatment of the surface by the head assembly.

In another form, the invention comprises a vehicle is
5 adapted to ride on the surface. A head assembly adapted to carry a device engages and treats the surface. An actuator on the vehicle supports the head assembly over the surface and is adapted to raise and lower the head assembly relative to the surface. A sensor detects a position of the head
10 assembly relative to the surface. A head position control, responsive to input from the operator, indicates a desired position of the head assembly relative to the surface. A driving circuit responsive to the head position control and responsive to the sensor energizes the actuator to raise and
15 lower the head assembly so that the position of the head assembly relative to the surface as detected by the sensor corresponds to the desired position as indicated by the head position control thereby controlling the relative engagement between the head assembly and the surface and thereby
20 controlling the treatment of the surface by the head assembly.

In another form, the invention comprises a head assembly is adapted to carry a device for engaging the surface. An actuator raises and lowers the head assembly
25 relative to the surface. A position control responsive to operator input indicates a head position of the device relative to the surface or range of head positions of the device relative to the surface. The head position or the range of head positions indicates a distance or range of
30 distances, respectively, between the device and the surface. A controller responsive to the position control selectively actuates the actuator to maintain the device in the head position or within the range of head positions as indicated by the position control.

35 In yet another form, the invention comprises a head assembly adapted to carry a device for engaging the surface.

An actuator raises and lowers the head assembly relative to the surface. A position control responsive to operator input indicates a repeatable head position of the device relative to the surface or a repeatable range of head positions of the device relative to the surface. The repeatable head position or the repeatable range of head positions indicates a distance or range of distances, respectively, between the device and the surface. A controller responsive to the position control selectively actuates the actuator to maintain the device in the repeatable head position or within the repeatable range of head positions as indicated by the position control.

Other objects and features will be in part apparent and in part pointed out hereinafter.

Brief Description of the Drawings

Figure 1 is a schematic block diagram of one preferred embodiment of a brush head positioning system according to the invention.

Figure 2 is a side plan view, partially in cross section, of one preferred embodiment of a brush head positioning system according to the invention wherein a linear potentiometer is employed to sense the position of the support relative to the brush head.

Figures 3 and 4 are block diagrams of preferred embodiments of a system according to the invention.

Figure 5 is a side plan view, partially in cross section, of one preferred embodiment of a brush head positioning system according to the invention shown in combination with a vehicle for supporting the system and shown with a brush attached to the brush head.

Figure 6 is a partial front cross sectional view taken along lines 5-5 of Figure 5 of the brush head positioning system of the invention.

Figure 7 is a graph illustrating the relationship between pressure applied to the brush head, current (torque)

driving the brush motors and position (actuator stroke) of the brush head of one preferred embodiment of a brush head positioning system according to the invention.

Figure 8 is schematic block diagram of one preferred embodiment of a brush head positioning system in combination with a vehicle according to the invention having controls for brush pressure, brush torque and brush position.

Corresponding reference characters indicate corresponding parts throughout the drawings.

10 Detailed Description of the Preferred Embodiments

Referring to Fig. 1, a block diagram of one preferred embodiment of the system according to the invention is illustrated. A vehicle 30 which rests on and traverses a floor 32 (or other surface) supports a motor 34 for driving a screw 36. Rotation of the screw causes a support nut 38 to move upward or downward, depending on the rotation of the screw. A compressible member 40, such as a coil spring, has one end 42 connected to and engaging the nut 38 and has a second end 44 connected to and engaging a head assembly 46. The compressible member is positioned within a tube (not shown). The details of this interconnection between the compressible member 40, the actuator 38 and the head assembly 46 is shown in more detail in Figs. 2, 5 and 6 below.

A linear potentiometer 48 is positioned between the nut 38 and the head assembly 46 and generates a voltage signal via line 50 which indicates the distance between the nut 38 and head assembly 46. This generated signal also indicates changes in the length of the compressible member 40. A driving circuit 52 selectively energizes the motor 34 to drive the screw 36. When the screw is driven in one direction (e.g., counterclockwise), the nut 38 moves upward away from the floor 32 thereby pulling the spring 40 and the head assembly 46 upward away from the floor 32. When the screw 36 is driven in the opposite direction (e.g.,

clockwise), the nut is driven downward toward the floor 32 causing the spring 40 and head assembly 46 to also move downward. This movement continues until the head assembly contacts the floor 32 at which point the compressible member 40 and linear potentiometer 48 begin to compress. An operator adjusts a head position potentiometer 52 on a control panel which indicates a desired position of the head assembly relative to the nut and which approximately indicates the desired position of the head assembly 46 relative to the floor 32. A comparator 54 compares the voltage signal provided via line 50 indicating the length of the linear potentiometer 48 to the voltage signal generated by the head position potentiometer 52. The voltage signals may be scaled to accommodate this comparison. When these signals correspond to each other indicating that the position of the head assembly 46 as indicated by the linear potentiometer 48 corresponds to the desired position of the head assembly as indicated by the position of the head potentiometer 52, the comparator 54 signals the driving circuit 52 and further energization of the motor 34 is discontinued.

When not in use, an operator places a brush up/down switch 56 in the "up" position which signals the driving circuit 52 to retract the to its upmost position. An optional upper limit sensor such as a switch 58 may be provided to sense the upmost position of the nut 38 and signal the driving circuit 52 to discontinue further energization of the motor 34. For example, the upper limit switch 58 may be a proximity sensor.

Fig. 2 illustrates one preferred embodiment of a portion of a vehicle according to the invention which is adapted to ride on a surface which is being treated. The lower portion of Fig. 2 illustrates a head assembly adapted to move up and down and adapted to carry a device for engaging and treating the surface. As shown in Fig. 2, the head assembly includes a brush head 61 having a brush plate

62 which engages brushes 63. Alternatively, brushes 63 may be replaced by pads or other cleaning devices. The brush head 61 terminates in an upwardly projecting flange 64 for engaging a variable length connector tube assembly 65 via a
5 brush head pivot pin 66. The tube assembly 65 includes a spring anchor 67 which is preferably a pin permanently positioned and placed across the tube assembly 65. Above the spring anchor 67 and within the tube assembly 65 is positioned a spring 68 which constitutes a compressible
10 member having one end connected to the head assembly 61. In particular, the lower end of spring 68 engages the brush head assembly 61 via spring anchor 67. The other end of the spring 68 is connected to and rests against a support nut 69 of a linear actuator. The lower end of nut 69 engages the
15 upper end of spring 68.

The nut 69 is positioned within the tube assembly 65 and moves axially within the assembly to compress or permit expansion of the spring 68. The tube assembly 65 includes opposing slots 70. An actuator pin 71 passing through the
20 nut 69 of the linear actuator rides upward and downward in the slots 70 of the tube assembly 65. The nut 69 is driven by a screw 72 rotated by a motor 73. The nut, screw and motor constitute the linear actuator on the vehicle which raises and lowers the brush head assembly 61 relative to the
25 vehicle. As a result, the brush head assembly 61 is raised and lowered relative to the surface on which the vehicle is positioned so that the relative engagement between the brushes 63 of the head assembly 61 and particularly brushes 63 and the surface is controlled. As a result, the
30 treatment of the surface by the brush is controlled.

A linear position sensor is located between the actuator tube assembly 65 and the linear actuator 69. As illustrated in Fig. 2, this sensor is implemented by a linear potentiometer 74 which is connected at one end to the
35 tube assembly 65 by a bolt 75 and which is connected at the other end to the actuator pin 71. Those skilled in the art

will recognize that other types of devices may be used to measure the distance between the nut 69 and the head assembly 61. Also, other position sensors may be used to determine the position of the head assembly relative to the floor. For example, a proximity or motion sensor may be positioned at the head assembly to detect its position on the floor.

As the nut 69 moves upward and downward, the spring 68 is expanded or compressed causing the linear potentiometer 74 to expand or contract and to measure the distance between the nut and head assembly. Referring again to Fig. 1, the voltage signal 50 generated by the linear potentiometer 48 (74 in Fig. 2) is provided to a comparator 54 and this voltage signal is compared to a voltage signal generated by the head positioned potentiometer 52. The comparator 54 provides a signal to the driving circuit 52 which signal is a function of the comparison between the linear potentiometer voltage signal 50 and the head position potentiometer voltage signal. When these signals correspond to each other, the driving circuit discontinues operation of the motor 34.

For example, assume that the voltage signal of the linear potentiometer varies from 15v to 5v as the spring is compressed. Also, assume that the voltage signal of the head position potentiometer varies from 15 v to zero, with zero volts corresponding to the down-most portion of the head assembly. If the signal from the head position potentiometer 52 is correspondingly larger than the signal 50 of the linear potentiometer 48, the driving circuit 52 energizes motor 34 to move the nut 38 upward to expand the linear potentiometer 74 so that the signal from the linear potentiometer increases until it corresponds to the signal from the head position potentiometer. Similarly, if the linear potentiometer voltage signal is correspondingly less than the head position potentiometer voltage signal, the comparator 54 provides a signal to the driving circuit 52

which causes the driving circuit to drive the motor 34 in such a manner to cause the nut 38 to move downward and compress the linear potentiometer 74 until the signals correspond. Preferably, the comparator 54 and driving circuit 52 are configured so that the actuator will not activate unless there is a difference between the potentiometer signal 50 and the head position potentiometer 52 of at least a certain amount, such as 0.06 volts. In other words, the actuator is not energized if the linear potentiometer signal and the head position potentiometer signal fall within a defined range or window of operation. Sensors, such as upper limit switch 58 and a lower limit switch (not shown), control the maximum up and the maximum down positions. For example, such limit switches on the actuator may sense the maximum positions.

Since several factors determine the amount of pressure applied between the brush head and the floor, the positioning system of the invention may not necessarily result in the application of a constant pressure. For example, the signals will vary within the window of operation. Therefore, the corresponding pressure will vary depending on the size of the window. In addition, the spring tends to weaken over time due to wear and tear and age. The system does not compensate for such weakening. Instead, the system consistently maintains head position. If pressure control in addition to position control is desired, the system of Fig. 8 may be employed.

In operation, the force of the brush is applied to the floor surface is determined by the weight of the brush head assembly 61 (approximately 80-90 lbs.) augmented by the variable force (50-200 lbs.) from the spring 68. The support nut 69 effectuates more or less compression to the spring 68 to increase or decrease the brush force. As illustrated in Fig. 2, the nut 69 is connected to the brush head assembly by the connector tube assembly 65 which has slots 70 therein. An actuator connecting pin 71 is placed

in the slots and rides in the slots in the tube. The spring 68 is sandwiched between the brush head and the end of the nut and is captured inside the tube assembly 65.

To raise the brush assembly 61, the brush up/down switch 56 is placed in the "up" position. This causes the driving circuit 52 to operate the motor 34 to drive the linear actuator to rotate screw 72 to move the nut 69 into its fully retracted and upward position. As a result, pin 71 engages the top of slots 70 to raise the tube assembly brush head until the nut reaches an upper limit as detected by the upper limit switch 58.

To lower the brush head assembly 61, switch 56 is placed in the "down" position. The linear actuator as controlled by the driving circuit 52 drives the nut 69 downward thereby lowering the brush head. The nut 69 will continue to move downward until the brushes 63 touch the floor. At this point, the nut begins to compress the spring 68 and the connecting pin 71 in the end of the actuator 69 begins to move downward within the slots 70 of the tube. As the connecting pin moves downward, it will compress the potentiometer. The nut will continue to move downward until the voltage signal of the linear potentiometer 74 reaches the corresponding voltage potential (or scaled value) of the potentiometer 52 set by the operator on the control panel.

When the brush encounters a depression in the floor, the linear actuator as controlled by the driving circuit 52 drives the nut downward thereby lowering the brush head. The nut 69 will compress the spring 68 and the connecting pin 71 will move downward in the slots 70 of the tube. As the connecting pin continues to move downward in the slots, it compresses the length of the potentiometer. The nut will continue to move downward until the voltage signal of the linear potentiometer 74 reaches the corresponding voltage potential (or scaled value) of the potentiometer 52 set by the operator on the control panel.

When the brush encounters a elevation in the floor, the linear actuator as controlled by the driving circuit 52 drives the nut upward thereby raising the brush head. The nut 69 will expand the spring 68 and the connecting pin 71 will move upward in the slots 70 of the tube. As the connecting pin continues to move upward in the slots, it expands the length of the potentiometer. The nut will continue to move upward until the voltage signal of the linear potentiometer 74 reaches the corresponding voltage potential (or scaled value) of the potentiometer 52 set by the operator on the control panel.

The driving circuit 52 and comparator 54 (Fig. 1) constitute a motor controller which compares the voltages of the linear potentiometer 48 with the control panel potentiometer 52. There is a minimum and maximum voltage setting programmed into the controller. The controller will tell the actuator to stop if the linear potentiometer reaches one of these settings. Pressing the "up" position on switch 56 will override these settings thus allowing the actuator to raise the brush head off the floor. The controller is configured to have a voltage window setting that compares the voltages (or scaled value) of the linear potentiometer to the panel potentiometer. The window is set such that small variations or movements of the linear potentiometer will not cause the actuator to move. This is to prevent constant adjustment of the actuator. It is also contemplated that the comparator and driving circuit constituting the motor controlling may be implemented digitally. For example, the linear potentiometer signal 50 and the voltage signal of potentiometer 52 may be digitalized by an A/D converter and the resulting digital signals compared by a digital processor which controls the actuator.

To change the brush force, the control panel potentiometer 52 is turned either to a higher or lower setting. The controller will then cause the motor to

activate to extend or retract the nut until the linear potentiometer reaches the corresponding voltage potential of the control panel potentiometer. The brush head assembly 61 can be raised at any time by pressing the "up" position of the rocker switch to raise the brush head off the floor. Pressing the down position of the switch will cause the brush head to lower. It will continue to lower until the linear potentiometer reaches its corresponding set position.

The automatic brush head positioning system according to the invention and as illustrated in Figs. 1 and 2 detects the floor position by monitoring the movement of the actuator/tube connecting pin 71. When the brush head assembly is in the "up" position (brush is off the floor) the connecting pin contacts and engages the top portion of the slots 70. When the brush head is lowered and the brushes contact the floor, the pin 71 will begin to move downward within the slots 70. By monitoring the relative position of the connecting pin to the tube assembly, the head positioning system can detect the position of the floor relative to the machine. If the brush wears or a different type of brush is used, the same brush position can be attained without having to change the control panel potentiometer settings. The brush head assembly will always return to the relative position of the connecting pin to the tube independent of the actual brush height. Also, as noted above, the head assembly will adjust to various floor surface contours using the same concept.

Fig. 3 is a block diagram of one preferred embodiment of a system 1 according to the invention. The system 1 includes a brush up/down switch 2 which is controlled by an operator to raise and lower a lower head assembly 4 relative to an upper head assembly 5 affixed to a vehicle. The lower head assembly 4 includes a brush 6 for engaging and treating a floor surface 8. When the operator actuates or closes switch 2, this indicates to the driving circuit 10 that a

drive motor 12 may be energized to raise or lower the head assembly 4. For example, switch 2 would be close circuited to indicate that the head assembly 4 should be lowered and switch 2 would be open circuited to indicate that the head assembly 4 should be raised. Initially, an operator would set a head position control 18 to indicate a desired position for the lower head assembly 4. For example, control 18 may be a potentiometer associated with a scale, display, index or other indicator indicating the desired position of the lower head assembly 4. The indicator may indicate inches of downward movement, inches from the floor or a percentage of either, or some other indicator of position. The motor 12 drives the head assembly up or down, such as by rotating a screw, and includes a position sensor 13 which indicates the position of the head assembly 4. For example, the motor may be Warner Actuator E150 position system. It includes an actuator internal position potentiometer which indicates the position of a screw which it drives. When switch 2 is closed by the operator to indicate that the head assembly should be lowered, driving circuit 10 continuously energizes motor 12 to lower the head assembly 4 until the head assembly 4 reaches a position corresponding to the position of the head position control 18. A comparator 24 or op-amp compares the signal provided by the position sensor 13 to a signal provided by the head position control 18. When these signals are nulled out or approximately equal, comparator 24 will provide a signal to the driving circuit 10 to discontinue energizing the motor 12. The driving circuit 10 will drive the head assembly up or down depending on which signal has a greater value. The comparator controls the driving circuit 10 to cause the motor 12 to rotate the screw driving the head assembly clockwise or counter clockwise to raise or lower the head assembly until its position matches the desired position as indicated by the control 18. If the operator sets control 18 to its maximum down position, the driving circuit 10 will

drive the head assembly to its fully extended position. If switch 2 is placed in the "up" position, the driving circuit 10 will drive the head assembly 4 to its fully retracted position. As shown in Fig. 3, an optional input from the position sensor 13 to the driving circuit indicates the position of the head assembly to the driving circuit. This optional input is particularly useful in digital systems.

In one respect, the system 1 of Fig. 3 is a position follower system. An actuator (motor 12 plus driving screw) downwardly extends and upwardly retracts the head assembly 4 in response to an operator's command as indicated by head position control 18. As the operator turns control 18, the reversible motor 12 turns the screw driving the head assembly 4 until the position sensor 13 matches the setting of control 18. One way to accomplish this position follower system is to have identical potentiometers for position sensor 13 and control 18 feeding the inputs of an op-amp which functions as the comparator 24. If the inputs to the op-amp are the same, the driving circuit 10 does not energize the motor 12. If the inputs are different, the motor 12 will rotate in the appropriate direction until the inputs are equal. If full "up" is indicated, the motor is operated to raise the head assembly until the position sensor indicates a value corresponding to the fully retracted position.

Fig. 4 is a block diagram of another preferred embodiment of a system 100 according to the invention. The system 100 includes a brush up/down switch 102 which is controlled by an operator to raise and lower a lower head assembly 104 relative to an upper head assembly 105. The head assembly 104 includes a brush 106 for engaging and treating a floor surface 108. When the operator actuates or closes switch 102, this indicates to the driving circuit 110 that a drive motor 112 may be energized to raise or lower the head assembly 104. Preferably, switch 102 would be closed to indicate that the head assembly 104 should be

lowered and switch 102 would be opened to indicate that the head assembly 104 should be raised. When switch 102 is closed to indicate that the head assembly should be lowered, driving circuit 110 continuously energizes motor 112 to
5 lower the head assembly 104 until the head assembly trips a touchdown switch 114 indicating that the head assembly 104 and brush 106 have reached a repeatable position such as in contact with the floor 108.

Once the touchdown switch 114 is tripped, a counter 116
10 is reset and the driving circuit 110 continues to lower the head assembly 104 and brush 106 according to a head position control 118 set by the operator. Control 118 indicates to the system 100 the additional distance by which the head assembly 104 and brush 106 should be lowered after the brush
15 106 comes in contact with the floor 108 and the touchdown switch 114 is tripped. Control 118 may optionally include a display indicating a percentage of the maximum additional distance by which the head 104 should be lowered or a display which indicates the actual distance selected by the operator. A hall sensor 120, associated with the motor 112,
20 monitors the rotations of the motor 112 thereby indicating the position of the head assembly 104 and the brush 106. The hall sensor 120 provides a series of pulses to counter 116 which are converted to an analog position signal by a digital to analog (D/A) converter 122. The analog signal is
25 provided to a comparator 124 and indicates the distance which the head assembly 104 and brush 106 have been lowered past the repeatable preset position at which point the touchdown switch 114 was tripped. The head position control
30 118, which may be a potentiometer, generates a desired position signal indicating the desired distance that the head assembly 104 and brush 106 should be lowered beyond the repeatable position. When the analog position signal corresponds to the desired position signal provided by the
35 head position control 118, comparator 124 signals driving circuit 110 to discontinue operation of motor 112 because

the brush is now in the position relative to the floor 108 to begin treatment.

Figs. 5 and 6 illustrate one preferred embodiment of a brush head positioning system according to the invention shown in combination with a vehicle 126 for supporting the system 100. Figs. 5 and 6 illustrate the system 100 with the brush 106 attached to the head assembly 104 although it is contemplated that the head assembly 104 may carry any device for engaging and/or treating the surface of the floor 108. The upper head assembly 105 is pivotally supported by a bulkhead 128 carried on the vehicle 126 and is connected to the bulkhead 128 by a pivot pin 130. A lower portion of the head assembly 104 is connected to the bulkhead 128 by parallel pivoting rods 132 which are connected by pivot pins 134 to the bulkhead 128 and which are also connected by pivot pins 136 to a support 138 which is part of the head assembly 104.

The upper portion of the head assembly 105 includes the motor 112 which drives a motor shaft 140 for rotating a plurality of gears 142 which mesh with each other to rotate a screw 144. A traveling nut 146 threadably engaging the screw 144 is raised or lowered by rotation of the screw 144 as caused by the motor 112 rotating its motor shaft 140 to rotate the gears 142. The nut 146 is covered by an inner tube 148 which is crimped to and moves with the nut 146. The inner tube 148 has an upwardly extending portion 150 which extends above the top of the nut to partially cover the screw 144 and to act as a stop. When the nut 146 is in its highest position, portion 150 abuts against a housing 151 for gears 142 and prevents the nut 146 from moving upward.

The nut 146 supports the lower portion of the head assembly 104 by a traveling nut pin 152 which engages the nut 146 and also engages an outer slotted tube 154 coaxial with the inner tube 148 and coaxial with screw 144 and nut 146. The outer slotted tube 154 slides along the inner tube

148 depending on the position of the lower portion of the head assembly 104. Two slots 156 in opposing sides of the outer slotted tube 154 form a guide within which the bolt 152 is positioned and moves. As illustrated in Figs. 5 and 6, the head assembly 104 is in the down position so that the brush 106 is engaging the floor 108. As illustrated in the down position, the pin 152 is located in the lower portion of the slot 156. The screw 144 has been rotated to move the nut 150 downward thereby causing a downward force on the pin 152 which allows the outer slotted tube 154 and the lower portion of the head assembly 104 to drop downward to touch the floor.

The lower end of the outer tube engages a bolt 158 which engages two supports 160 on opposite sides of the outer slotted tube 154. The supports 160 are connected to a platform 162 which supports a brush motor 164 which engages the brush 106 via an interlock 166 and causes the brush to rotate.

A compressible member such as a spring 168 is located between the lower end of the nut 146 and the bolt 158. When the head assembly 104 is in its raised position, traveling nut pin 152 is held in place at the top of the slots 156 by the biasing action of the spring 168 between the nut 146 and the bolt 158. As the nut is moved downward by rotation of the screw 144 to lower the head assembly 104, the traveling nut bolt 152 continues to be held in place at the top of the slot 156 by the spring 168. However, when the brush 106 comes in contact with the surface of floor 108, further downward movement of the lower portion of the head assembly 104 is inhibited. As a result, the continued movement of the nut 146 downward causes the traveling nut pin 152 to slide downward in the slots 156 thereby compressing the spring 168.

A bracket 170 is mounted to the motor 112 by a U-clamp 172 and is supported in a position parallel to the screw 144 and nut 146. The lower portion of the bracket 170 includes

a slot 174 which is engaged by two screws 176 which support a switch 178. The switch may be positioned anywhere along the slot 174 so that it may be moved up or down relative to the lower portion of the head assembly 104. The switch 178
5 has a trip bar 180 which extends toward the outer tube 154 and is positioned immediately above the traveling nut pin 152. The pin 152 has a sleeve or extension 182 which engages the underside of the trip bar 180. The position of switch 178 and trip bar 180 define a repeatable position to
10 which the lower portion of the head assembly 104 may be moved. The trip bar 180 is a flexible member which has a fully extended, unflexed position and a flexed position. As shown in phantom in Fig. 2 and referred to by reference character 184, when the lower portion of the head assembly
15 104 and traveling nut pin 152 are in the raised position, trip bar 182 is in the flexed position. As the screw 144 rotates to move the nut 146 downward, nut pin 152 moves downward until it eventually reaches a point at which the trip bar 180 is in an unflexed, fully extended position.
20 This point trips switch 178 and defines the repeatable position of the head assembly. When switch 178 is positioned within slot 174 so that it is tripped when the brush 106 touches the surface of floor 108, it functions as touchdown switch as illustrated in Fig. 1B. As a touchdown
25 switch, it defines the repeatable position as the position at which the brush touches the floor.

Assuming that switch 178 is positioned as touchdown switch 114 to indicate when the brush 106 contacts the surface of floor 108, the system 100 would operate as
30 follows. Initially, an operator would set the head position control 118 to define a preset distance by which the head assembly 104 should be lowered once it reaches the repeatable position in contact with floor 108. Next, the operator would position the brush up/down switch 102 in the
35 down position indicating to the driving circuit 110 that motor 112 should be operated to rotate screw 144. This

causes the traveling nut 146 to move downward relative to the screw 144 and the upper portion 105 of the head assembly 104. As the nut moves downward, traveling nut pin 152 also moves downward. When pin 152 reaches a point such that trip
5 bar 180 is in its fully extended position, switch 178 is tripped to indicate that the brush 106 has reached the repeatable position and is in contact with the surface of floor 108. At this point, counter 116 is reset to zero and continued energization of the driving circuit is controlled
10 by the comparator 124. Comparator 124 compares the desired position signal provided by head position control 118 to the analog position signal corresponding to the count in counter 116 and indicating the actual position of the lower portion of the head assembly 104 and brush 106. The count in
15 counter 106 is generated by a magnet 186 positioned on one of the gears 142 which rotates with the screw 144. As a result, the number of pulses or counts generated each time the magnet 142 passes the hall sensor 120 corresponds to the number of rotations of the screw 144 which in turn
20 corresponds to the position of the nut 146. Additional magnets may be added to the gear to increase the resolution of the system. When the counter 116 includes a count of pulses which corresponds to a rotation of the screw 144 which corresponds to the position of traveling nut 146 which
25 corresponds to the setting of the head position control 118, the comparator 124 shuts down the driving circuit 110. Essentially, the additional preset amount that the nut 146 is moved after the repeatable position is approximately equal to the distance or amount by which the spring 168 is
30 compressed. Therefore, this amount is directly proportion to the amount of force that is being applied by the brush 106 to the surface of floor 108.

As illustrated in Figs. 5 and 6, the motor 112, gears 142, screw 144, and nut 146 constitute an actuator raising
35 and lowering the head assembly 104 relative to the surface of the floor 108 thereby controlling the relative engagement

between the head assembly and the surface and in particular, controlling the relative engagement between the brush 106 and the surface. This controls the treatment of the surface by the brush. Switch 178 constitutes a sensor for detecting the repeatable position of the head assembly. The driving circuit 110 is responsive to the switch to lower the head assembly an additional preset amount as defined by the head position control 118 after the switch 178 detects that the head assembly has reached the repeatable position. As a result, the additional preset amount has been defined by input from the operator.

The nut 146 constitutes a support which is connected to the actuator and is raised and lowered by the actuator. The spring becomes a compressible member between the nut 146 or support and the lower portion of the head assembly 104. By positioning the switch 178 as shown in Figs. 2 and 3 and noted above, it becomes a compression sensor detecting compression of the spring 168 when the support is lowered by the actuator. It is also contemplated that other types of compression sensors (or force sensors) may be used to detect compression of the spring 168. It is also contemplated that the switch 178 may be mounted directly on outer tube 154 to detect when the nut pin 152 leaves the up most position within slots 156.

It should be recognized that the touchdown switch 114 which is implemented in Figs. 5 and 6 as switch 178 is an optional aspect of the invention to determine the repeatable position. Those skilled in the art will recognize other ways for establishing a repeatable position such as other types of position sensors. In addition, the hall sensor 120 and magnet 186 function as an encoder (detector) to provide a continuous count indicating the position of the travelling nut 146. There-fore, a particular count corresponds to the repeatable position and could be determined by continuously monitoring the count in counter 116. For example, if the driving circuit were a microprocessor based circuit it would

be possible to continuously monitor the count of counter 116 knowing that one setting of the count would correspond to a repeatable preset position and another setting for the count would correspond to the additional preset amount defined by
5 the head position control 118.

In another aspect of the invention, it has been found that it is preferable to support the vehicle 126 by a plurality of pneumatic tires 188 rather than some type of rigid tire or other rigid structure. It has been found that
10 such pneumatic tires provide an added level of flexibility with regard to the positioning of the brush 106 on the surface of floor 108. This added flexibility allows the brush 106 to more easily float on the surface of the floor 108 providing a more even cleaning operation. In the
15 embodiment illustrated in Figs. 1 and 2, pneumatic tire may obviate the need for a compressible member and make the spring 40 of Fig. 1 and the spring 68 of Fig. 2 optional.

In another aspect of the invention, it is contemplated that the touchdown switch 114 of Fig. 4 may be used in
20 combination with the embodiment illustrated in Fig. 3. For example, when an operator closes switch 2 to lower the head assembly 4, the driving circuit would energize the motor 12 until the head assembly 4 engages floor 8 and trips the touchdown switch. Thereafter, the driving circuit 10 would
25 drive the head assembly upward or downward an amount corresponding to the setting of the head position control 18. In this embodiment, the control 18 would control the distance of the head above or below the point at which the brush 6 engages the floor 8.

It is also contemplated that the touchdown switch may be a force or position sensor which would sense when the brush contacts the floor. For example, the touchdown switch may be an optical sensor sensing that the brush is in
30 contact with the floor, or it may be a proximity sensor, a current (torque) sensor or a force sensor on the head
35 assembly and/or motor which would indicate that the head is

in contact with the floor. When the head contacts the floor, any further downward movement of the head will result in an upward force on the head assembly and motor, which upward force may be detected by a force sensor on the head assembly or motor.

Fig. 7 is a graph illustrating the relationship between the pressure applied by the brush 106 to the surface of the floor 108, the current or torque driving the brush motor 166 and the position or actuator stroke of the brush 106 relative to the surface of floor 108. The z axis represents the amount of pressure being applied by the brush 106 to the surface floor 108. There is a point at which the pressure becomes a maximum. Beyond a maximum pressure P_{MAX} , damage to the brush or to the floor surface or to the brush motor or to another part of the system may occur. Therefore, the maximum pressure P_{MAX} defines a plane which constrains the operation of the system 100.

Current or torque applied to the brush motor 166 is graphed along the x axis. As with the pressure, there is a maximum current I_{MAX} or maximum torque which is predefined. Beyond this maximum current I_{MAX} , damage to the brush motor 166 may occur or excessive torque may be applied to the floor or some other damage may occur to the system. The maximum current I_{MAX} defines a plane which constrains the operation of the system 100.

The stroke or distance by which the brush is moved is graphed along the y axis. As with pressure and current, there is a maximum stroke L_{MAX} beyond which damage to the head, system or floor may occur. This maximum stroke L_{MAX} defines a plane which constrains the operation of the system 100.

Viewing Fig. 7 as a whole, it can be seen that the operation of the system 100 is constrained by three orthogonal planes which define a rectanguloid R within which the system 100 is constrained to operate.

Fig. 8 is a schematic block diagram of one preferred embodiment of a brush head positioning system in combination with a vehicle according to the invention having controls for brush pressure, brush torque and brush position. Fig. 8 illustrates a system which operates within the constraints of the rectanguloid R of Fig. 7. The system 200 includes a vehicle 202 for supporting a head assembly 204. The head assembly includes a pressure sensor 206 for measuring the pressure which a brush 208 applies to a surface of a floor 210. The head assembly 204 also includes an actuator 212 for moving the brush 208 toward or away from the floor 210. In addition, the head assembly 204 includes a brush motor 214 for rotating the brush 208.

The pressure sensor 206 provides a signal to a controller 216 which controls the actuator 212 via a driving circuit 218 and which also controls the current of the brush motor 214 via a current control 220. By controlling the current, the torque of the brush 208 applied to the floor 210 is also controlled. Hence, the controller provides a torque control signal to the current control 220.

The system 200 also includes a memory 222 which is programmed with the maximum information illustrated in Fig. 7. In particular, the memory is programmed with the maximum current, maximum pressure, and maximum stroke. The system 200 also includes operator controls 224 including a torque control 226, a head position control 228 and a pressure control 230. The operator is permitted to set these controls anywhere within the acceptable operating region as defined by the rectanguloid R. In particular, the torque control 226 can be set between zero torque and the maximum torque (I_{MAX}). The head position control 228 can be set by the operator anywhere between the zero stroke point and the maximum stroke point (L_{MAX}). Also, the pressure control 230 may be set anywhere between zero pressure and maximum pressure (P_{MAX}). By setting these three controls, the

operator defines a point within the rectanguloid R for operation of the system 200.

In operation, the controller 216 responds to the torque control 226 to provide a torque control signal to the current control 220 thereby controlling the torque and current of the brush motor 214. Similarly, the controller 216 is responsive to the head position control 228 for selectively energizing the driving circuit 218 to drive the actuator 212 to maintain a certain position for the brush 208 relative to the floor 210. In addition, the controller 216 is responsive to the pressure control 230 for selectively energizing the driving circuit 218 so that the actuator 212 positions the brush 208 on the floor 210 to maintain constant pressure.

Although not illustrated in Fig. 8, one of ordinary skill in the art will recognize that the actuator 212 may provide feedback information, such as encoder or position sensor information as noted above with regard to Figs. 3, 5 and 6, to the controller 216 to indicate the position of the brush 208. In addition, the current control 220 may provide feedback information to the controller 216 to indicate the actual current of the brush motor 214. In another aspect of the invention, it is contemplated that any one of the three controls may be designated as a dominant control and that the other two controls may be designated as limit controls. For example, if torque control is of primary interest, the torque control 226 would be set by the operator to indicate the desired torque. The head position control 228 would be set by the operator to indicate the maximum stroke and the pressure control 230 would be set by the operator to indicate the maximum pressure. In operation, the torque control 226 would indicate the desired torque to the controller 216 which would control the current control 220 to maintain the desired torque of brush motor 214 as long as the stroke limit as indicated by head position control 228

and the pressure limit as indicated by pressure control 230 are not exceeded.

In another aspect of the invention, it is contemplated that all three controls may specify maximums or limits and that the system 200 would be permitted to operate according to some algorithm or other procedure within the limits set by the operator controls 224. For example, the controller 216 may be programmed with a cleaning algorithm which would optimize the torque, stroke, and pressure controls in order to accomplish the maximum cleaning capability of the brush 208 on floor 210. Alternatively, the controller 26 may also be programmed with a polishing algorithm which would optimize polishing. In these embodiments, the torque control 226 would specify the maximum torque, the head position control would specify the maximum stroke, and the pressure control 230 would specify the maximum pressure by which the algorithms would be permitted to operate. An algorithm for maximizing battery life may also be employed. For example, the maximum pressure and current may be reduced in order to extend the run-time of a battery-powered apparatus of the invention.

It is also contemplated that the pressure control could be a separate control from the actuator. For example, a hydraulic system may be used to determine and monitor the pressure of the brush 208 on the floor 210 independent of the position of the actuator 212.

It is also contemplated that any of the above described embodiments may include displays indicating actual pressure, torque (or current) and/or position to assist the operator in setting or adjusting the controls. For example, a 10 segment bar graph may be positioned adjacent the head position control to indicate motor current. This would also permit the operator to repeat the same cleaning parameters. Alternatively, the systems of the invention may include a memory for storing various operator settings so that the

operator could program the memory and recall the parameter settings as needed.

In view of the above, it will be seen that the several objects of the invention are achieved and other advantageous results attained.

As various changes could be made in the above products without departing from the scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

WHAT IS CLAIMED IS:

1. An apparatus for use on a surface and responsive to an operator, said apparatus comprising:

a vehicle adapted to ride on the surface;

5 a head assembly adapted to carry a device for engaging and treating the surface;

a support;

a connector assembly interconnecting the head assembly and the support;

10 an actuator on the vehicle for raising and lowering the support relative to the surface;

a sensor detecting a distance between the support and the head assembly;

15 a head position control, responsive to input from the operator, indicating a desired position of the head assembly relative to the support; and

a driving circuit responsive to the head position control and responsive to the sensor for energizing the actuator to raise and lower the support so that the distance
20 between the support and the head assembly as detected by the sensor corresponds to the desired position as indicated by the head position control thereby controlling the relative engagement between the head assembly and the surface and thereby controlling the treatment of the surface by the head
25 assembly.

2. The apparatus of claim 1 wherein the sensor comprises a linear potentiometer.

3. The apparatus of claim 2 wherein the head position control is a operator-controlled potentiometer and further comprising a comparator for comparing a voltage signal generated by the operator-controlled potentiometer to a
5 voltage signal generated by the linear potentiometer, said comparator providing an output signal corresponding to the comparison to the driving circuit.

4. The apparatus of claim 1 further comprising an up/down switch responsive to the operator and connected to the driving circuit for selectively controlling the actuator such that when the switch is in an UP position, the actuator
5 is energized to raise the support and such that when the switch is in a DOWN position, the actuator is energized to lower the support.

5. The apparatus of claim 1 wherein the connector assembly has a first end engaging the head assembly and having a second end engaging the support wherein a distance between the first end and the second end is variable.

6. The apparatus of claim 5 wherein the support is a traveling nut, wherein the actuator comprises a motor rotating a screw which engages and drives the traveling nut, said nut being raised and lowered by rotation of the screw,
5 and wherein the connector assembly comprises:

a slotted tube having a slot at one end receiving a pin sliding within the slot, the pin connected to the traveling nut, the tube supporting the head assembly at its other end;
and

10 a compressible member within the tube having one end engaging the nut and having another end engaging the tube;
and

wherein the sensor comprises a linear sensor detecting a length of the compressible member.

7. An apparatus for use on a surface and responsive to an operator, said apparatus comprising:

a vehicle adapted to ride on the surface;

a head assembly adapted to carry a device for engaging
5 and treating the surface;

an actuator on the vehicle supporting the head assembly over the surface and adapted to raise and lower the head assembly relative to the surface;

a sensor detecting a position of the head assembly
10 relative to the surface;

a head position control, responsive to input from the operator, indicating a desired position of the head assembly relative to the surface; and

a driving circuit responsive to the head position
15 control and responsive to the sensor for energizing the actuator to raise and lower the head assembly so that the position of the head assembly relative to the surface as detected by the sensor corresponds to the desired position as indicated by the head position control thereby
20 controlling the relative engagement between the head assembly and the surface and thereby controlling the treatment of the surface by the head assembly.

8. The apparatus of claim 7 further comprising:

a support connected to the actuator and being raised and lowered by the actuator;

a connector assembly including a compressible member
5 between the support and the head assembly;

wherein the sensor comprises a distance sensor connected between the support and the head assembly for detecting a distance between the support and the head assembly; and

10 wherein the driving circuit responds to the distance sensor to control the head position of the head assembly relative to the surface to maintain contact between the head assembly and the surface.

9. The apparatus of claim 8 wherein the distance sensor is a linear potentiometer.

10. The apparatus of claim 7 further comprising:

a support adapted to be raised and lowered by the actuator;

a compressible member of variable length between the
5 support and the head assembly; and

wherein the sensor comprises a linear sensor detecting a length of the compressible member.

11. The apparatus of claim 7 wherein the actuator comprises a motor rotating a screw driving a traveling nut
10 engaging the screw, said nut being raised and lowered by rotation of the screw, and further comprising:

a slotted tube having a slot at one end receiving a pin sliding within the slot, the pin connected to the traveling nut, the tube supporting the head assembly at its other end;
15 and

a compressible member within the tube having one end engaging the nut and having another end engaging the tube; and

wherein the sensor comprises a linear sensor detecting
20 a length of the compressible member.

12. The apparatus of claim 11 further comprising an inner tube coaxial with and slidable within the slotted tube, the inner tube connected to and moving with the support.

13. The apparatus of claim 11 wherein the sensor comprises a detector for providing a count corresponding to the position of the head, wherein the head position control is set by the operator to indicate the additional preset
5 amount and further comprising a comparator for comparing the count to the additional preset amount, said driving circuit being responsive to comparator to lower the traveling nut below a repeatable position when the count corresponds to a position which is higher than the additional preset amount
10 as indicated by the head position control.

14. The apparatus of claim 13 wherein the detector comprises a magnet adapted to rotate in synchronism with the screw, a Hall sensor detecting rotation of the magnet and providing a pulse, and a counter for counting the pulses of
5 the Hall sensor, and wherein the comparator compares the count of the counter to the additional preset amount.

15. The apparatus of claim 14 further comprising a switch for detecting when the nut is in the repeatable position and wherein the switch resets the counter and wherein the driving circuit is responsive to the comparator
5 to lower the traveling nut a number of counts corresponding to the additional preset amount.

16. The apparatus of claim 11 wherein the sensor comprises a switch on the tube for detecting compression of the compressible member wherein the repeatable position corresponds to the position of the device when it engages the surface.

17. The apparatus of claim 7 wherein the sensor comprises a switch on the actuator for detecting a position of the head assembly.

18. The apparatus of claim 7 further comprising a vehicle having pneumatic tires for riding on the surface, said vehicle supporting the actuator such that the head assembly is above or on the surface.

19. An apparatus for use on a surface and responsive to an operator, said apparatus comprising:

- a head assembly adapted to carry a device for engaging the surface;
- 5 an actuator raising and lowering the head assembly relative to the surface;

a position control responsive to operator input for indicating a head position of the device relative to the surface or range of head positions of the device relative to the surface, said head position or said range of head positions indicating a distance or range of distances, respectively, between the device and the surface; and

a controller responsive to the position control for selectively actuating the actuator to maintain the device in the head position or within the range of head positions as indicated by the position control.

20. The apparatus of claim 19 further comprising:
a motor on the head assembly for rotating the device;
a torque control circuit having an input receiving a signal for controlling the torque of the motor;

a torque control responsive to operator input for indicating a desired torque or a desired range of torques for the motor; and

wherein the controller is responsive to the torque control for providing a torque control signal to the input of the torque control circuit to maintain the motor at the desired torque or within the desired range of torques.

21. The apparatus of claim 20 further comprising:
a pressure sensor detecting the pressure of device on the surface;

a pressure control responsive to operator input for indicating a desired pressure or a desired range of pressures for the device on the surface; and

wherein the controller is responsive to the pressure control and the pressure sensor for selectively actuating the actuator to maintain the pressure of the device on the surface at the desired pressure or within the desired range of pressures.

22. The apparatus of claim 19 further comprising:

a pressure sensor detecting the pressure of device on the surface;

5 a pressure control responsive to operator input for indicating a desired pressure or a desired range of pressures for the device on the surface; and

wherein the controller is responsive to the pressure control and the pressure sensor for selectively actuating the actuator to maintain the pressure of the device on the surface at the desired pressure or within the desired range of pressures.

23. An apparatus for use on a surface and responsive to an operator, said apparatus comprising:

a head assembly adapted to carry a device for engaging the surface;

5 an actuator raising and lowering the head assembly relative to the surface;

a position control responsive to operator input for indicating a repeatable head position of the device relative to the surface or a repeatable range of head positions of the device relative to the surface, said repeatable head position or said repeatable range of head positions indicating a distance or range of distances, respectively, between the device and the surface; and

15 a controller responsive to the position control for selectively actuating the actuator to maintain the device in the repeatable head position or within the repeatable range of head positions as indicated by the position control.

BRUSH HEAD POSITIONING SYSTEMAbstract of the Invention

An apparatus for use on a surface and responsive to an operator. A head assembly is adapted to carry a device for
5 engaging the surface. An actuator raises and lowers the head assembly relative to the surface. A position control responsive to operator input indicates a head position of the device relative to the surface or range of head
10 positions of the device relative to the surface. The head position or the range of head positions indicates a distance or range of distances, respectively, between the device and the surface. A controller responsive to the position control selectively actuates the actuator to maintain the device in the head position or within the range of head
15 positions as indicated by the position control. As a result, a repeatable position or range of positions of the brush head is obtained, the relative engagement between the head assembly and surface is controlled and the treatment of the surface by the head assembly is controlled. Position
20 control may be used in combination with torque control of motors driving brushes for engaging the surface. Position control may also be used in combination with a pressure control measuring the pressure between the brush head and the surface.




FIG. 2




FIG. 3




FIG. 4





FIG. 7






FIG. 5

FIG. 6





FIG. 8



DECLARATION AND POWER OF ATTORNEY

REGULAR OR DESIGN APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

BRUSH HEAD POSITIONING SYSTEM

the specification of which:

(check one)

☒ [X] is attached hereto

☐ [] was filed on _____ as Application Serial No.

_____, and was amended on _____.

☐ [] was described and claimed in PCT International Application No. _____, filed on _____ and as amended under PCT Article 19 on _____, if any.

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56.

PRIORITY CLAIM

I hereby claim foreign priority benefits under Title 35, United States Code, §119 (a) - (d) or §365(b) of any foreign application for patent or inventor's certificate, or §365(a) of any PCT application which designates at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Priority Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)

Priority Not Claimed

ANY FOREIGN APPLICATION(S), ON THE SAME SUBJECT MATTER WHICH HAS A FILING DATE EARLIER THAN THE EARLIEST APPLICATION FROM WHICH PRIORITY IS CLAIMED

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)
-------------------	--------------------	---------------------------------

CLAIM FOR BENEFIT OF PROVISIONAL APPLICATION(S)

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below.

_____ (Application Number)	_____ (Filing Date)
_____ (Application Number)	_____ (Filing Date)

**CLAIM FOR BENEFIT OF EARLIER U.S. APPLICATION(S)
UNDER 35 U.S.C. 120**

(complete this part only if this is a divisional,
continuation or CIP application)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s), or §365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

<u>09/177,311</u>	<u>10/22/98</u>	<u>pending</u>
(Serial No.)	(Filing Date)	(Status)
<u> </u>	<u> </u>	<u> </u>
(Serial No.)	(Filing Date)	(Status)

POWER OF ATTORNEY

I hereby appoint the following attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Irving Powers (15,700), Donald G. Leavitt (17,626), John K. Roedel, Jr. (25,914), Michael E. Godar (28,416), Edward J. Hejlek (31,525), William E. Lahey (26,757), Richard G. Heywood (18,224), Frank R. Agovino (27,416), Kurt F. James (33,716), G. Harley Blosser (33,650), Paul I. J. Fleischut (35,513), Vincent M. Keil (36,838), Robert M. Evans, Jr. (36,794), Robert M. Bain (36,736), Joseph A. Schaper (30,493), Kathleen M. Petrillo (35,076), David E. Crawford, Jr. (38,118), Paul A. Maddock (37,877), Richard L. Bridge (40,529), Christopher M. Goff (41,785), James E. Butler (40,931), Derick E. Allen (43,468), Matthew L. Cutler (43,574), Michael G. Munsell (43,820), Karen Y. Hui (44,785), Anthony R. Kinney (44,834), Brian P. Klein (44,837), Sarah J. Chickos (46,157), Donald W. Tuegel (45,424), Steven M. Ritchey (46,321), Michael J. Thomas (39,857), and Kathryn J. Doty (40,593), all of the law firm of SENNIGER, POWERS, LEAVITT & ROEDEL, One Metropolitan Square, 16th Floor, St. Louis, Missouri 63102.

Send Correspondence To:

Direct Telephone Calls To:

Customer Number: 000321

Frank R. Agovino
(314) 231-5400

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor William Stuchlik

Inventor's signature _____ Date _____

Residence _____ Citizenship US

Post Office address 2100 Highway 265

Springdale, Arkansas 72764

Full name of second joint inventor Lenard Deiterman

Second inventor's signature _____ Date _____

Residence _____ Citizenship US

Post Office address 2100 Highway 265

Springdale, Arkansas 72764

Full name of third joint inventor Marvin Curtis

Third inventor's signature _____ Date _____

Residence _____ Citizenship US

Post Office address 2100 Highway 265

Springdale, Arkansas 72764

Full name of fourth joint inventor Gerald Courtney

Fourth inventor's signature _____ Date _____

Residence _____ Citizenship US

Post Office address 2100 Highway 265

Springdale, Arkansas 72764

Full name of fifth joint inventor James Keazer


Fifth inventor's signature _____ Date _____

Residence _____ Citizenship US

Post Office address 2100 Highway 265

Springdale, Arkansas 72764

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present:
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present:
for scanning. (Document title)

There were only 5 pages in Declaration

☐ Scanned copy is best available.